QuMax for Teltonika RUT956/RUT955

Integrated outdoor multi-band high power LTE directional antenna + outdoor Wi-Fi omni antenna + GPS antenna + place to install Teltonika RUT956 or RUT955 (All-in-one)

QuMAX offers the most powerful directional LTE antenna of all QuWireless antennas. It is dedicated to connections with long distance to base station. It is designed to have Teltonika **RUT956, RUT955 or RUT906** router installed inside IP67 enclosure. It is the first choice for fixed installations in industrial environment. **It has embedded also GPS antenna and outdoor Wi-Fi omni antennas.**

4G LTE | Wi Fi 2.4GHz | GPS | 694-2700MHz | 6 dBi | DIRECTIONAL | IP 67 | -40° TO +80°



LTE ANTENNA SPECIFICATION

FREQUENCY	694 - 960 MHz 1.7 - 2.2 GHz 2.2 - 2.7 GHz
SUPPORTED LTE/5G BANDS	1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 53, 65, 66, 67, 68, 69, 85, 103, n80, n81, n82, n83, n84, n86, n89, n90, n95, n97, n98, n100, n101, n256
GAIN	694 - 960 MHz : 4 dBi 1.7 - 2.2 GHz : 5 dBi 2.2 - 2.7 GHz : 6 dBi
FRONT-TO-BACK	>8 dB
VSWR	<1.30, max <1.80
BEAMWIDTH	90°/90° ±30°
POLARIZATION	Vertical
IMPEDANCE	50 Ω
CONNECTOR	2x SMA
CABLE TYPE	RG316

Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

WI-FI ANTENNA SPECIFICATION

FREQUENCY	2.4 - 2.5 GHz
GAIN	6 dBi
VSWR	<1.70, max <2.00
BEAMWIDTH	360°/25° ±5°
POLARIZATION	Vertical
IMPEDANCE	50 Ω
CONNECTOR	2x RPSMA
CABLE TYPE	RG316

GPS ACTIVE ANTENNA SPECIFICATION

FREQUENCY	1.56 – 1.61 GHz
VSWR	< 2
GAIN	3 dBi
GAIN 3V	28 dBi
DC POWER INPUT	2.5 V ~ 6.5 V
POWER CONSUMPTION	2.5-6.5mA
IMPEDANCE	50 Ω
POLARIZATION	RHCP (right hand circularly polarized)
CONNECTOR	1x SMA

Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

CABLE TYPE	RG174

MECHANICAL SPECIFICATION

RADOME MATERIAL	UV-resistant ASA
OPERATING HUMIDITY	up to 100% RH
MATERIALS	aluminum, PTFE, Fiberglass
CONNECTOR TYPE	RJ45 + 2xNf + 2xNm in external omni wi-fi antenna
INGRESS PROTECTION	IP67
DIMENSIONS	272 x 276 x 96 mm 10.71 x 10.87 x 3.78 inch
WEIGHT	1.8 kg 3.97 lbs
OPERATING TEMPERATURE	From -40°C to 80°C From -40°F to 176°F
ENCLOSURE RECOMMENDED TIGHTENING TORQUE	0.6 - 0.8 Nm
MAST DIAMETER	25-66mm 0.98-2.60 inch

Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

FREQUENCY BANDS

LTE / 4G GSM	694 MHz	5	8	12	13	14	17	18	960 MHz
		19	20	26	27	28	29	44	
		67	68	85	103	n81	n82	n83	
		n89	n100						
LTE / 4G UMTS	1710 MHz	1	2	3	4	9	10	25	2170 MHz
		33	34	35	36	37	39	n80	
		n84	n86	n95	n98	n101			
LTE / 4G WCS DARS	2300 MHz	30	40	n97					2400 MHz
LTE / 4G	2400 MHz	7	38	41	53	69	n90		2700 MHz

Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

PLOTS

VSWR for Wi-Fi antenna



VSWR for LTE antenna



Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

Gain for Wi-Fi antenna



Gain for LTE antenna



Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

LTE from 700MHz to 900MHz

ELEVATION



AZIMUTH



LTE from 1.71GHz to 2.17GHz

ELEVATION



AZIMUTH



Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

LTE from 2.3GHz to 2.7MHz

ELEVATION



AZIMUTH



Wi-Fi 2.4GHz and 5GHz

ELEVATION



AZIMUTH



Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

DIMENSIONS



Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.



WWW.QUWIRELESS.COM

Sales email: sales@quwireless.com **Tel:** +48 513 900 416

Support email: support@quwireless.com **Website:** www.quwireless.com

Address: Wireless Instruments Sp. z o.o., ul. Kościuszki 27, 52-116 Iwiny, Poland

Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.