


QuMax for Peplink MAX Transit Duo Pro

INTEGRATED MULTI-BAND 5G DIRECTIONAL ANTENNA + WIFI OMNI ANTENNA + GPS ANTENNA + PLACE TO INSTALL PEPLINK MAX TRANSIT DUO PRO (ALL-IN-ONE)

QuMax all-in-one antenna for Peplink MAX Transit Duo Pro router is dedicated to connections with long distance to base station. It has embedded directional 5G, Wi-Fi and GPS antenna. If you use MAX Transit Duo Pro with QuMax Omni antenna, you get an integrated complete solution with embedded router and multi band antennas in one enclosure. It is the first choice for fixed installations in industrial environment.

5G**Wi Fi**
DUALBAND
2.4GHz
5GHz**GPS**
617-6000MHz
6 dBi
DIRECTIONAL
IP 67
-40° TO +80°

OUTDOOR ANTENNA WORKS IN ANY
WEATHER CONDITIONS, IP67




ANTENNA PERFECTLY MATCHED WITH
THE PEPLINK MAX TRANSIT DUO PRO



ALL ANTENNAS AND PEPLINK ROUTER
INTEGRATED IN ONE ENCLOSURE



MADE IN **EUROPE**



5G/LTE SPECIFICATION

FREQUENCY	617 - 960 MHz 1.7 - 2.7 GHz 3.3 - 4.6 GHz 4.7 - 6.0 GHz
SUPPORTED LTE BANDS	1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 46, 47, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, 106
SUPPORTED 5G BANDS	n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n46, n47, n48, n53, n65, n66, n67, n71, n77, n78, n79, n80, n81, n82, n83, n84, n85, n86, n89, n90, n95, n97, n98, n100, n101, n256
GAIN	617 - 960 MHz : 6 dBi 1.7 - 2.7 GHz : 7 dBi 3.3 - 4.6 GHz : 7 dBi 4.7 - 6.0 GHz : 5.5dBi
VSWR	<2.00, max <3.00
BEAMWIDTH	80°/80° ±15°
POLARIZATION	Vertical
IMPEDANCE	50 Ω

WI-FI SPECIFICATION

FREQUENCY	2.4 - 2.5 GHz 5.0 - 7.2 GHz
GAIN	2.4 - 2.5 GHz: 6dBi 5 GHz: 7.5dBi 7 GHz: 7.5dBi
VSWR	< 1.50, max < 2.00
BEAMWIDTH	360°/25° +/- 5°
POLARIZATION	Vertical
IMPEDANCE	50 Ω

MECHANICAL SPECIFICATION

MATERIAL	BS, aluminum, PTFE, Fiberglass
INGRESS PROTECTION	IP67
CONNECTOR TYPE	RJ45
DIMENSIONS	486.0 x 292.2 x 210 mm 19.13 x 11.50 x 8.27 inch
WEIGHT	1.8 kg 3.97 lbs
OPERATING TEMPERATURE	From -40°C to 75°C From -40°F to 167°F

MOUNTING KIT

DIMENSIONS

9.9 x 10.5 x 14.8 cm
3.9 x 4.13 x 5.83 inch

REGULATION RANGE

+/- 30°

MAST DIAMETER RANGE

25 - 60mm
0.98-2.36 inch

MATERIAL

Polyamide with fiberglass + galvanized steel U-Bolts

WEIGHT


0.87kg

MOUNTING PLACE


Wall or mast or ceiling

PLOTS


VSWR for 5G/LTE antenna




VSWR for Wi-Fi antenna




Gain for 5G/LTE antenna




Gain for Wi-Fi antenna




5G/LTE Port 1/3 from 650MHz to 950MHz




5G/LTE Port 1/3 from 1.71GHz to 2.17GHz




5G/LTE Port 1/3 from 2.3GHz to 2.7GHz




5G/LTE Port 1/3 from 3.3 GHz to 3.8 GHz




5G/LTE Port 1/3 from 4.2 GHz to 4.6 GHz




5G/LTE Port 1/3 from 5.0 GHz to 5.9 GHz




5G/LTE Port 2/4 from 650 MHz to 950 MHz




5G/LTE Port 2/4 from 1.71 GHz to 2.17 GHz




5G/LTE Port 2/4 from 2.3 GHz to 2.7 GHz




5G/LTE Port 2/4 from 3.3 GHz to 3.8 GHz




5G/LTE Port 2/4 from 4.2 GHz to 4.6 GHz



5G/LTE Port 2/4 from 5.0 GHz to 5.9 GHz



Wi-Fi From 2.4 GHz to 6.5 GHz



DIMENSIONS

