


# QuSector S24-14HV-30-2

**QuSector S24-14HV-30-2 offers a 30 degrees, 14dBi gain signal with two 2.4GHz connectors. It is a perfect indoor and outdoor device for industrial installations.**

QuSector S24-14HV-30-2 is a single band, H&V polarity, MIMO 2x2 panel antenna. Two connectors operate at 2.4GHz with 14dBi gain. Due to its medium gain, it can be used on short or medium distances, for example for hotspots in schools, stadiums, offices or public places. High quality injection moulded enclosure allows to implement it alongside with indoor and IP68 outdoor solutions. The antenna comes with two 70cm (28inch) cables. The antenna comes with 2\*70cm (28inch) cables terminated with Nm, RPSMA, RPTNC connectors.



 **OUTDOOR ANTENNA WORKS IN ANY WEATHER CONDITIONS, IP68**

 **ANTENNA PERFECTLY MATCHED WITH THE ROUTER**

 **WALL OR MAST MOUNTING SYSTEM WITH TWO PLANES, 60 DEGREES REGULATION**

 **MADE IN EUROPE**



## WI-FI SPECIFICATION

<b>FREQUENCY</b>	2.3 - 2.7GHz
<b>GAIN</b>	14 dBi
<b>VSWR</b>	< 1.80
<b>BEAMWIDTH</b>	30°/30°
<b>POLARIZATION</b>	Horizontal Vertical
<b>IMPEDANCE</b>	50 $\Omega$
<b>SEPARATION BETWEEN CONNECTORS</b>	> 32dB
<b>FRONT-TO-BACK</b>	> 30dB
<b>MAX INPUT POWER</b>	50W
<b>DC GROUND</b>	Yes

## MECHANICAL SPECIFICATION

<b>MATERIAL</b>	ABS
<b>CONNECTOR</b>	2xRPSMA/2xNM/2xRPTNC
<b>OUTER DIMENSIONS</b>	29.2 x 48.6 x 10.6 cm 11.5 x 19.13 x 4.17 inch
<b>WEIGHT</b>	2.5 kg
<b>OPERATING TEMPERATURE</b>	-40°C to +80°C -40°F to 176°F

## MOUNTING KIT

<b>DIMENSIONS</b>	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
<b>REGULATION RANGE</b>	+/- 30°
<b>MAST DIAMETER RANGE</b>	25 - 66mm 0.98-2.60 inch
<b>MATERIAL</b>	Polyamide with fiberglass + galvanized steel U-Bolts
<b>MOUNTING PLACE</b>	Wall or ceiling or mast

## COMPATIBLE ROUTERS

VARIANT: SS24.14HV.30.2RS

<b>TELTONIKA</b>	RUT900, RUT901, RUT950, RUT951, RUT955, RUT956
<b>ROBUSTEL</b>	R1520 Global, R1520-4L (S), R1520-4L (V), R2010, R2011
<b>D-LINK</b>	DAP-2310, DAP-2360
<b>ERICSSON (CRADLEPOINT)</b>	IBR600C
<b>ROBUSTEL</b>	R1520 Global, R1520-4L (S), R1520-4L (V), R2010, R2011
<b>TELTONIKA</b>	RUT900, RUT901, RUT950, RUT951, RUT955, RUT956
<b>WAVETEL</b>	W240 4G/LTE

VARIANT: SS24.14HV.30.2RT


**VARIANT: SS24.14HV.30.2NM**
**RAJANT**

BreadCrumb ES1-2450CS, BreadCrumb LX5-2255B, BreadCrumb LX5-2255C, BreadCrumb LX5-2295C, BreadCrumb LX5-2455D, BreadCrumb LX5-2955C, Hawk BreadCrumb FE1-2450 / FE1-2450A, Peregrine LTE BreadCrumb FE1-2455LS, Peregrine LTE BreadCrumb FE1-2455LW, Sparrow BreadCrumb ME5-2450CS


**RAJANT**

BreadCrumb ES1-2450CS, BreadCrumb LX5-2255B, BreadCrumb LX5-2255C, BreadCrumb LX5-2295C, BreadCrumb LX5-2455D, BreadCrumb LX5-2955C, Hawk BreadCrumb FE1-2450 / FE1-2450A, Peregrine LTE BreadCrumb FE1-2455LS, Peregrine LTE BreadCrumb FE1-2455LW, Sparrow BreadCrumb ME5-2450CS

## PLOTS

**From 2.4GHz to 2.5GHz**


From 2.4GHz to 2.5GHz



## DIMENSIONS

