


QuSector S24-19HV-20-2 Nf

QuSector S24-19HV-20-2 offers a 20 degrees, 19dBi gain signal with two 2.4GHz connectors. It is a perfect indoor and outdoor device for industrial installations.

QuSector S24-19HV-20-2 is a single band, H&V polarity, MIMO 2x2 panel antenna. Two connectors operate at 2.2 - 2.5 GHz with 19dBi gain. Due to its medium gain, it can be used on short or medium distances, for example for hotspots in schools, stadiums, offices or public places. High quality injection moulded enclosure allows to implement it alongside with indoor and IP67 outdoor solutions. The antenna comes in with 2*Nf connectors.



OUTDOOR ANTENNA WORKS IN **ANY WEATHER CONDITIONS**, IP67



ANTENNA **PERFECTLY MATCHED** WITH THE ROUTER



WALL OR MAST MOUNTING SYSTEM WITH **TWO PLANES, 60 DEGREES REGULATION**



MADE IN **EUROPE**



WI-FI SPECIFICATION

FREQUENCY	2.2 - 2.5 GHz
GAIN	19 dBi
VSWR	<1.40, max <1.70
BEAMWIDTH	20°/20°
POLARIZATION	Horizontal Vertical
IMPEDANCE	50 Ω
SEPARATION BETWEEN CONNECTORS	> 32dB
FRONT-TO-BACK	> 25dB
MAX INPUT POWER	50W
DC GROUND	Yes

MECHANICAL SPECIFICATION

MATERIAL	ABS
CONNECTOR	2xNf
OUTER DIMENSIONS	390 x 392 x 80 mm 15.35 x 15.43 x 3.14 inch
WEIGHT	2.5 kg
OPERATING TEMPERATURE	-40°C to +80°C -40°F to 176°F

MOUNTING KIT

DIMENSIONS

9.9 x 10.5 x 14.8 cm
3.9 x 4.13 x 5.83 inch

REGULATION RANGE

+/- 30°

MAST DIAMETER RANGE

25 - 66mm
0.98-2.60 inch

MATERIAL

Polyamide with fiberglass + galvanized steel U-Bolts

MOUNTING PLACE

Wall or ceiling or mast

COMPATIBLE ROUTERS

VARIANT: SS24.19HV.20.2NF

TELTONIKA

RUT900, RUT901, RUT950, RUT951, RUT955, RUT956

ROBUSTEL

R1520 Global, R1520-4L (S), R1520-4L (V), R2010, R2011

RAJANT

BreadCrumb ES1-2450CS, BreadCrumb LX5-2255B, BreadCrumb LX5-2255C, BreadCrumb LX5-2295C, BreadCrumb LX5-2455D, BreadCrumb LX5-2955C, Hawk BreadCrumb FE1-2450 / FE1-2450A, Peregrine LTE BreadCrumb FE1-2455LS, Peregrine LTE BreadCrumb FE1-2455LW, Sparrow BreadCrumb ME5-2450CS

COMSET

CM210A-W, CM210Q-W, CM685V-1, CM685V-4, CM685V-6, CM685V-6-G

D-LINK

DAP-2310, DAP-2360

ERICSSON (CRADLEPOINT)

IBR600C, W4005

PROROUTE

H685 LTE 4G CAT6 Router, H685 WRT M2M 5G Router, H900 5G Router

RAJANT
ROBUSTEL
TELTONIKA
WAVETEL
WLINK

BreadCrumb ES1-2450CS, BreadCrumb LX5-2255B, BreadCrumb LX5-2255C, BreadCrumb LX5-2295C, BreadCrumb LX5-2455D, BreadCrumb LX5-2955C, Hawk BreadCrumb FE1-2450 / FE1-2450A, Peregrine LTE BreadCrumb FE1-2455LS, Peregrine LTE BreadCrumb FE1-2455LW, Sparrow BreadCrumb ME5-2450CS

R1520 Global, R1520-4L (S), R1520-4L (V), R2010, R2011


RUT900, RUT901, RUT950, RUT951, RUT955, RUT956

W240 4G/LTE, W4600, W4600-S2



R220, R520

PLOTS

From 2.4GHz to 2.5GHz



From 2.4GHz to 2.5GHz



DIMENSIONS

