# QuShell 62G

**QuShell 5G 4x4MIMO, 5G/LTE 2x2MIMO, WiFi 6e 2x2MIMO is a high performance mobility antenna providing performance connectivity across diverse frequencies and applications for 5G/4G/LTE.**

QuShell 5G 4x4MIMO, 5G/LTE 2x2MIMO, 2x2MIMO WiFi 6e is a high performance mobility antenna providing performance connectivity across diverse frequencies and applications for **5G/4G/LTE**. It offers optional GPS/GNSS and up to 2x2 MIMO/Diversity configurations at 2.4/5.0/7.2GHz for Wi-Fi. The optional high-performance GPS/GNSS antenna features an integrated 18dB gain LNA. **Dedicated for Teltonika RUTM52.**
It comes with **4x 5G, 2x 5G/LTE, 1x GPS/GNSS** and **2x Wi-Fi** antennas. It covers a wide range from **580 to 6350 MHz** for 5G/LTE bands and additionally dual-band Wi-Fi 6e antennas provide concurrent **2.4 GHz and 5 to 7.2 GHz**. The QuShell 5G/LTE finds its place in public **sector industry** (busses, firetrucks, ambulances), marine environments, tourism and various IoT systems. The set consists of marine, surface and **pole/wall mounting brackets** allowing to install QuShell on a roof, mast, pole, wall or other flat surfaces. Standard cable length is 50cm. For other variants please contact your local reseller or account manager.






# WI-FI SPECIFICATION

| | |
|---|---|
| FREQUENCY | 2.4 - 2.5 GHz<br>5 - 7.2 GHz |
| MAX. GAIN | 2.4 - 2.5 GHz: 2dBi<br>5 - 7.2 GHz: 5dBi |
| VSWR | < 2.50 |
| BEAMWIDTH | 360°/25° |
| POLARIZATION | Vertical |
| IMPEDANCE | 50 Ω |
| MAX INPUT POWER | 50W |
| DC GROUND | Yes |

# 5G/LTE SPECIFICATION

| | |
|---|---|
| FREQUENCY | 0.58 - 2.0 GHz<br>2.0 - 3.5 GHz<br>3.5 - 5.0 GHz<br>5.0 - 6.35 GHz |
| MAX. GAIN | 0.58 - 2.0 GHz : 2 dBi<br>2.0 - 3.5 GHz : 3.2 dBi<br>3.5 - 5.0 GHz : 3.1 dBi<br>5.0 - 6.35 GHz : 3.8 dBi |
| SUPPORTED LTE BANDS | 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 65, 66, 67, 68, 69, 70, 71, 74, 75, 76, 85, 103, 106, 107, 111, 252, 253, 254, 255, 256 |


Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

| | |
|---|---|
| SUPPORTED 5G BANDS | n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n24, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n46, n47, n48, n50, n51, n53, n54, n65, n66, n67, n68, n70, n71, n74, n75, n76, n77, n78, n79, n80, n81, n82, n83, n84, n85, n86, n89, n90, n91, n92, n93, n94, n95, n97, n98, n99, n100, n101, n105, n106, n109, n110, n250, n251, n252, n253, n254, n255, n256 |
| VSWR | <2.50, max <3.00 |
| BEAMWIDTH | 360°/35° ±5° |
| POLARIZATION | Vertical |
| IMPEDANCE | 50 Ω |

## MECHANICAL SPECIFICATION

| | |
|---|---|
| MATERIAL | ASA |
| CONNECTOR | 2xRPSMA & 7xSMA |
| OUTER DIMENSIONS | 160 x 160 x 90 mm<br>6.3 x 6.3 x 3.54 inch |
| WEIGHT | 1.5 kg |
| OPERATING TEMPERATURE | -40°C to 80°C<br>-40°F to 176°F |
| CABLE TYPE | RG174 |


Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

# MOUNTING KIT

| | |
|---|---|
| MATERIAL | Galvanized steel |
| WEIGHT | 0.4kg |
| MOUNTING PLACE | Wall or mast |
| MAST DIAMETER | 25-66 mm<br>0.98-2.60 inch |

# PLOTS

## 5G/LTE VSWR





Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

## 5G/LTE GAIN




## WiFi - X VSWR






Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

## WiFi - X GAIN




## WiFi - V VSWR






Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

## WiFi - V GAIN




## 5G/LTE from 617MHz to 960MHz

ELEVATION




AZIMUTH





Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

## 5G/LTE from 1.71GHz to 2.5GHz

ELEVATION




AZIMUTH




## 5G/LTE from 3.3GHz to 4.2GHz

ELEVATION




AZIMUTH





Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

## 5G/LTE from 4.8GHz to 5.8GHz

ELEVATION




AZIMUTH




## Wi-Fi X Port 1 From 2.4 GHz to 6.5 GHz

ELEVATION




AZIMUTH





Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

## Wi-Fi X Port 2 From 2.4 GHz to 6.5 GHz

ELEVATION




AZIMUTH




## Wi-Fi V From 2.4 GHz to 6.5 GHz

ELEVATION




AZIMUTH





Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.

# CONNECTORS




QuWireless
WWW.QUWIRELESS.COM
**Sales email:** sales@quwireless.com
**Tel:** +48 513 900 416
**Support email:** support@quwireless.com
**Website:** www.quwireless.com
**Address:** Wireless Instruments Sp. z o.o., ul. Kościuszki 27, 52-116 Iwiny, Poland

Copyright © 2023, Wireless Instruments. Specifications and information given in this document are subject to change without prior notice.